

Volume Unit series	Connectivity	Directivity Sensor beam/ degrees	Logistic app included	Battery lifetime/ years*	Casing	Thermal conditions (Celcius)	Network range****	Weight	Size	Multiple sensor coordinated settings	Logistic Programming flexibility
VU 100	GSM	75	No	8 **	PC/ABS Re-usable	-40 to +80	35 km	370 g	135x85x25mm	Yes	Yes
VU150	WiFi	75	No	8 **	PC/ABS Re-usable	-40 to +80	50 mtr	370 g	135x85x25mm	Yes	Yes
VU 200 WB - ultrasonic	NB-IoT	75	Yes	26***	PC/ABS Re-usable	-40 to +80	10-15 km	175 g	75x65x25mm	Yes	Yes
VU 250 NB - ultrasonic	NB-IoT	15	Yes	26***	PC/ABS Re-usable	-40 to +80	10-15 km	175 g	75x65x25mm	Yes	Yes
VU 280 ToF - optical	NB-IoT	18	Yes	26***	PC/ABS Re-usable	-40 to +80	10-15 km	160 g	75x65x25mm	Yes	Yes
VU 300 WB - ultrasonic	LoRa WAN	75	Yes	26***	PC/ABS Re-usable	-40 to +80	5-10 km	175 g	75x65x25mm	Yes	Yes
VU 350 NB - ultrasonic	LoRa WAN	15	Yes	26***	PC/ABS Re-usable	-40 to +80	5-10 km	175 g	75x65x25mm	Yes	Yes